



PRODUCT SHEET

ECO RUB HYDRO METAL PROTECTIVE PAINT

- Gloss finish
- Interior and Exterior application
- Low VOC
- Great protective power
- Long lasting for exterior applications
- Ecolabel Certified

USAGE: Galvanized metal and ferrous metal for urban, industrial and maritime applications

COVERAGE: 320 to 440 sq. foot per gallon. Purchase the amount necessary to finish your project.

SURFACE PREPARATION: Surfaces should be dry and carefully cleaned to remove dust, mildew, grease, wax, dirt, rust and old adhesive paint.

APPLICATION: Brush and roller: ready to use. Airless gun: dilute by 4 to 6%. Apply 2 coats.

THINNING: Use water.

DRY TIME: At 77°F and 65% humidity dry time:

- to dry: 6 hours
- to recoat: 24 hour

CLEAN UP: Remove excess of paint before washing tools with water.

DISPOSAL: Do not dispose through the drain and take it to waste collection program.

PHYSICAL PROPERTIES

- VOC: <31g/L
- Binder: Glycerophthalic resin
- Density: 1.28
- Dry extract: 54%
- Dry extract volume ratio: 44%
- Specular gloss: >60%

LIMITATIONS: Keep away from children. Keep from freezing. Do not apply when the surface or air temperature is below 41°F or above 90°F. Do not store paint for more than 12 month.

DISCLAIMER: *The present data sheet cancels and replaces any previous documents of this mark. Its goal is to inform our customers about our product's properties. These indications are based on our current knowledge. However, they can replace an appropriate descriptive of the nature and condition of the surface to be painted. As technique is in everlasting development, it belongs to our customers, before any use, to check with our services if the present form hasn't been changed recently.*