


| | |
|--|---------------------------------------|
|  | PRODUCT SHEET |
| | ECOPRO MATTE ACRYLIC PAINT |

- Interior paint
- Low VOC
- Low odor
- Only available in White base
- Great hiding power
- Easy to apply

USAGE

- Indoor: dry rooms Great for drywalls and ceilings. Can be applied directly on bricks, plaster, concrete, cement, wallpaper.

COVERAGE: 320 to 480 sq. foot per gallon. Purchase the amount necessary to finish your project.

SURFACE PREPARATION: Remove old adhesive paint. After cleaning the surface, apply a primer such as EcoPro PRIM.

APPLICATION: When using a brush or a roller, dilute the paint by 0 to 3%. When using an airless sprayer, dilute the paint by 5 to 7%.

THINNING: Use water.

DRYING TIME: At 77°F and 65% humidity dry time:

- to touch: 20 minutes
- to dry: 30 minutes
- to recoat: 6 hours

CLEAN UP: Remove excess of paint before washing tools with water.

DISPOSAL: Do not dispose through the drain and take paint to a waste collection program.

PHYSICAL PROPERTIES

- VOC: 40g/L
- Binder: Acrylic copolymer
- Density: matte 1.56
- Dry extract: 62%
- Dry extract volume ratio: 39%

LIMITATIONS: Keep away from children. Keep from freezing. Do not apply when the surface or air temperature is below 41°F. Do not store paint for more than 12 month.

DISCLAIMER: *The present data sheet cancels and replaces any previous documents of this mark. Its goal is to inform our customers about our product's properties. These indications are based on our current knowledge. However, they can replace an appropriate descriptive of the nature and condition of the surface to be painted. As technique is in everlasting development, it belongs to our customers, before any use, to check with our services if the present form hasn't been changed recently.*