

	PRODUCT SHEET
	ECOTOP PRIM ACRYLIC PRIMER / FINISHING PAINT

- Matte finish
- Zero VOC
- No odor
- Ecolabel certified
- Easy to apply
- All purpose paint
- Great hiding power

USAGE: Dry rooms, sealing plaster, plaster and plaster by-products, concrete and cement plaster, old adhesive paints.

COVERAGE: 280 to 360 sq. foot per gallon. Purchase the amount necessary to finish your project.

SURFACE PREPARATION: Surfaces should be dry and carefully cleaned to remove dust, mildew, grease, wax, dirt and old adhesive paint. Apply a fixing agent on powdery or very porous supports. Apply 2 coats on new walls. Dilute paint by 5% with water for the first coat. Apply an anti-rust primer for metal applications.

APPLICATION: Brush and roller: dilute by 0 to 3%. Airless gun: dilute by 5 to 7%. Apply 2 coats.

THINNING: Use water. EcoTopPrim can be mixed with universal colorants.

DRY TIME: At 77°F and 65% humidity dry time:

- to dry: 30 minutes
- to recoat: 6 hours

CLEAN UP: Remove excess of paint before washing tools with water.

DISPOSAL: Do not dispose through the drain and take it to waste collection program.

PHYSICAL PROPERTIES

- VOC: 0g/L
- Binder: Acrylic based emulsion
- Density: 1.57
- Dry extract:
- Dry extract volume ratio:
- Specular gloss:

LIMITATIONS: Keep away from children. Keep from freezing. Do not apply when the surface or air temperature is below 41°F or above 90°F. Do not store paint for more than 12 month.

DISCLAIMER: *The present data sheet cancels and replaces any previous documents of this mark. Its goal is to inform our customers about our product's properties. These indications are based on our current knowledge. However, they can replace an appropriate descriptive of the nature and condition of the surface to be painted. As technique is in everlasting development, it belongs to our customers, before any use, to check with our services if the present form hasn't been changed recently.*