



PRODUCT SHEET

ECOTOP WOOD

HIGH PERFORMANCE, HUMIDITY REGULATOR MICROPOROUS SEMI-GLOSS WOOD PAINT

- Interior and exterior semi-glossy paints
- Low odor
- Durable and washable gloss finish
- Water clean-up
- Easy to apply
- Great darkening ability
- Ecolabel certified

USAGE: All types of wood traditionally used in construction for outdoors and indoors purposes (hardwoods, conifers, tropical woods), clean pre-painted woods.

COVERAGE:

- 280 sq. foot per gallon on absorbing woods.
- 440 sq. foot per gallon on non-absorbing woods.

SURFACE PREPARATION: Resinated area should be cleaned with a chlorinated or aromatic solvent. Wood should be sandpapered and cleaned to remove grease and dirt. Painted wood should be carefully washed and non-adhesive paint removed.

APPLICATION: On fresh wood, we recommend to first apply a layer diluted by 15 to 20% in order for the paint to deeply penetrate the wood and ensure a great adherence for the 2nd coats. When using a brush or a roller, dilute by 0 to 5%. When using a sprayer, dilute by 12 to 15%. When dipping the wood directly into the paint, dilute by 10 to 20% and apply 1 or 2 coats.

THINNER: Water.

DRY TIME: At 77°F and 65% humidity dry time:

- to touch: 30 minutes
- to dry: 1 hour
- to recoat: 2 hours

CLEAN UP: Remove excess of paint before washing tools with water.

DISPOSAL: Do not dispose through the drain and take it to a waste collection program.

PHYSICAL PROPERTIES

- VOC: <45g/L
- Binder: Acrylic emulsion
- Density: 1.29
- Dry extract: 56%
- Dry extract volume ratio: 43%

LIMITATIONS: Keep away from children. Keep from freezing. Do not apply when the surface or air temperature is below 41°F or above 86°F. Do not store paint for more than 12 month.

DISCLAIMER: *The present data sheet cancels and replaces any previous documents of this mark. Its goal is to inform our customers about our product's properties. These indications are based on our current knowledge. However, they can replace an appropriate descriptive of the nature and condition of the surface to be painted. As technique is in everlasting development, it belongs to our customers, before any use, to check with our services if the present form hasn't been changed recently.*